



IKA

STIRRING AND MIXING

Ideal stirrers for your stirring and mixing tasks in the lab. IKA lab stirrers and overhead stirrers stand out due to their indispensable features. A broad spectrum of stirring tools is the key to successful mixing. Functionality, safety, and longevity are the main goals in the development of IKA's stirrers.

Overhead Digital Stirrer:

- Digital speed display
- Infinitely adjustable speed
- Push-through agitator shafts
- Overload protection
- Slim casing
- Quiet operation

Overhead Wireless Control Stirrers:

- Removable Wireless Control
- Multilingual TFT display
- Programmable functions
- Interval operation
- Timer function
- Reverse Function (100 Control)

Overhead Mechanical Stirrer:

- Digital display
- Constant power-drive
- Two speed ranges
- Push-through agitator shafts
- Slimline design

Magnetic Stirrer Hot Plate

- Glass ceramic top available in three sizes
- Speed range from 100 to 1500 rpm
- Temperature range from 50 to 500°C



STIRRER SPECIFICATIONS

Digital

Order Code	13514-10 Eurostar 40	13516-20 Eurostar 60
Stirring Quantity Max (H2O)	25 L	40 L
Speed Range	0/30 - 2000 rpm	0/30 - 2000 rpm
Maximum Viscosity	30000 mPas	50000 mPas
Setting Speed Accuracy	+/- 1 rpm	+/- 1 rpm
Weight	10 lbs (4.4 kg)	10 lbs (4.4 kg)
Chuck	accepts .5-10 mm	accepts .5-10 mm
Electrical Input	115V, 50/60 Hz	115V, 50/60 Hz
USB / RS 232 Interface	No / No	No / No
Torque Max	40 Ncm (3.5 in-lbs)	60 N-cm (5 in-lbs)

Control

Order Code	13517-30 Eurostar 60	13518-02 Eurostar 100
Stirring Quantity Max (H2O)	40 L	100 L
Speed Range	0/30 - 2000 rpm	0/30 - 1300 rpm
Maximum Viscosity	50000 mPas	70000 mPas
Setting Speed Accuracy	+/- 1 rpm	+/- 1 rpm
Weight	10 lbs (4.7 kg)	10 lbs (4.7 kg)
Chuck	accepts .5-10 mm	accepts .5-10 mm
Electrical Input	115V, 50/60 Hz	115V, 50/60 Hz
USB / RS 232 Interface	Yes / Yes	Yes / Yes
Torque Max	60 Ncm (5 in-lbs)	100 Ncm (9 in-lbs)

Digital

Order Code	13523-10 RW 20	
Stirring Quantity Max (H2O)	20 L	
Speed Range	72-600 / 288-2400 rpm	
Maximum Viscosity	10000 mPas	
Setting Speed Accuracy	+/- 1 rpm	
Weight	7 lbs (3.1 kg)	
Chuck	accepts .5-10 mm	
Electrical Input	115V, 50/60 Hz	
USB / RS 232 Interface	No / No	
Torque Max	150 Ncm (13 in-lbs)	

Also Available...

Contact us for more information and accessories.

